

Fabric Vertical Blinds

89 mm louvers

BEFORE INSTALLATION:

Louver for each blind are separately packed in plastic bags, please pair the louvers, weights and chains, and headrail for each blind.

NOTE:

TO PREVENT DAMAGE and FACILITATE EASY FITTING – do not release the blind before mounting or PULL IT BACK UP before you perform STEPS 1-3.

STEP 1.


The Brackets.

There are basically two types of fixing:

- top fixing -- to ceiling or to lintel (window recess top);
- face fixing -- to wall or window frame;

Your blinds come with universal

galvanized
'twister'
brackets



that are used for both types of blind fitting. This type of bracket is good enough to hold your blind in place for years. The easy operation twister mechanism lets you remove blind at any time for slats cleaning, room painting, etc.

We recommend locking brackets to the blind's headrail before you start fixing them to wall/ceiling to see how the twister mechanism locks and to realize that the brackets must allow for blind cords mechanisms located in blind's headrail.

STEP 2.

Fixing the brackets.

We recommend that you make your measurements and markings for brackets positioning on wall/ceiling individually for each blind!

Install brackets need to be fixed to the ceiling/lintel every 70-100cm, eg 4 brackets for one 200cm blind to evenly support the weight of blind.

RECOMMENDATION:

Position brackets in headrail in places they will be locked. Determine the blind fitting position (or take measurements between brackets) then make markings in pencil on the wall/ceiling pointing to brackets location. Do the drilling and fix the brackets to wall/ceiling.

STEP 3.

Installing the headrail and louvers.

- Click the headrail into brackets **[please note that for joint blinds you need to mount the headrails so that the controls are left and right hand side, not in the middle].**
- Click the louvers into moving supports inside of the headrail.

STEP 4.

Preparing the Blind.

- a) Once the louvers hang on the headrail, close the blind and put weights into pockets at louvers bottoms, with chain eye up.
- b) Use the ball chains (2 per blind) to connect the weights and **you're done.**

NOTE: If lifting or tilting mechanism do not work smoothly*** – **DO NOT FORCE OPERATION** - unlock brackets, dismount blind and check if brackets do not interfere with the cords inside headrail.